



Republic of the Philippines  
**SOUTHERN LUZON STATE UNIVERSITY**  
Lucban, Quezon

**REQUEST FOR QUOTATION**

**ULTRASONIC PULSE VELOCITY TESTER (PDO)**

**Purchase Request No. 2023-02-0316**  
**Approved Budget for the Contract: ₱ 150,000.00**


The Southern Luzon State University through the Bids and Awards Committee invites interested firms/supplier to submit quotation for the procurement of Ultrasonic Pulse Velocity Tester (PDO) to apply the sum of One Hundred Fifty Thousand Pesos Only (₱ 150,000.00) inclusive of VAT, being the Approved Budget for the Contract (ABC), details as follows:

Qty.	Unit	ITEM/S DESCRIPTION
1	set	Ultrasonic Pulse Velocity tester for crack analysis (complete with accessories and training)

1. The quotation must be submitted (can also be send thru email at the contact details listed below) or to the Office of the Procurement Office/Bids and Awards Committee, Southern Luzon State University, 2<sup>nd</sup> Flr. Hermano Puli Building, and shall be received by the Committee.

E-mail : [slsuprocurement2021@gmail.com](mailto:slsuprocurement2021@gmail.com)

2. The SLSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. Southern Luzon State University SLSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.

  
**Samuel T. Sacopla**  
Head, Procurement office  
Southern Luzon State University  
Lucban, Quezon  
Tel. No.: (042)540-6519





Microprocessor incorporated

Battery operated by internal rechargeable battery pack (2400 Mah) and External Charger

14 Working hours using 1 Hz pulse rate

RS 232 output for PC or printer

Connectable to oscilloscope

Transit time measurement from 0.1 to 1999.9 microseconds

Pulse rate 1, 2, 5, 10 per second, selectable

Resolution 0.1 microseconds

Trasnutter output 1200 V

Frequency range 24 to 150 kHz

Receiver input impedance 1 Mohm

Weight of the tester 0.5 kg, complete set 2.3 kg