



Republic of the Philippines
SOUTHERN LUZON STATE UNIVERSITY
Lucban, Quezon

REQUEST FOR QUOTATION

CAMERA (OIAA)

Purchase Request No. 2024-01-0043
Approved Budget for the Contract: ₱ 110,000.00


The Southern Luzon State University through the Bids and Awards Committee invites interested firms/supplier to submit quotation for the procurement of **Camera (OIAA)** to apply the sum of **One Hundred Ten Thousand Pesos Only (₱ 110,000.00) inclusive of VAT**, being the **Approved Budget for the Contract (ABC)**, details as follows:

Qty.	Unit	ITEM/S DESCRIPTION
1	lot	Mirrorless Camera with 18-55mm Kit Lens, Small Ring Charger and Battery
		*see attached document for reference

1. The quotation must be submitted (can also be send thru email at the contact details listed below) or to the Office of the Procurement Office/Bids and Awards Committee, Southern Luzon State University, 2nd Flr. Hermano Puli Building, and shall be received by the Committee.

E-mail : slsuprocedurement2021@gmail.com

2. The SLSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/ informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. Southern Luzon State University SLSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.


MARIDEL C. ZABELLA
Head, Procurement Office
Southern Luzon State University
Lucban, Quezon
Tel. No.: (042)540-6519



Republic of the Philippines
SOUTHERN LUZON STATE UNIVERSITY
 Lucban, Quezon

REQUEST FOR QUOTATION

Office/End-User:	OIAA	Date:	
COMPANY NAME:		PR No.:	2024-01-0043
ADDRESS :			
TEL. NO./FAX NO. :		TIN No.:	

Please quote your lowest price on the item(s) listed below, subject to the Terms & Conditions stated below and submit your quotation duly signed by your representative not later than _____ of _____ in the return envelope attached herewith to the Procurement office.

- TERMS and CONDITIONS**
1. All entries must be typewritten or legibility written.
 2. Delivery period within _____ upon conforme of the approved Purchase Order (P.O). Administrative penalties to Sec. 69 of the Revised IRR-RA 1984 shall be imposed for non-delivery without valid reason.
 3. Warranty shall be for a minimum of three (3) months for Supplies & Materials; (1) one year for Equipment from date of acceptance by the end-user.
 4. Price validity shall be for a period of sixty (60) calendar days.
 5. Suppliers required to submit updated documents yearly such as G-EPS Resgistration, Certificate of Tax, Mayor's Permit, DTI, Bank Name/Account and Branch for evaluation of the Procurement Office upon submission of the quotation.
 6. Bidders shall submit complete specifications showing products certification, if applicable.
 7. Please indicate the brand for each items being offered.
 8. The Approved budget ceiling for this procurement is PHP 110,000.00

MARIDEL C. ZABELLA
 Head, Procurement Office

Item #	Qty.	Unit	ITEM/S DESCRIPTION	Unit Price	Total Cost
1	1	lot	Mirrorless Camera with 18-55mm Kit Lens, Small Ring Charger and Battery		
			*see attached document for reference		

Source of Fund: _____ Warranty: _____
 Delivery Period: _____ Price Validity: _____
After having carefully read & accepted your General Conditions, We quote you on the item(s) at prices note above. If the space of providec on the Delivery Period, Warranty & Price Validity are left blank, it means that I concur w/ the Terms & Conditions specified by SLSU Procurement Office.

Printed Name/Signature/Date

**Fujifilm X-S20 with XF 18-55mm Kit
Lens Mirrorless Camera**

₱110,000.00



KEY FEATURES:

- 26.1MP APS-C X-Trans BSI CMOS 4 Sensor
- X-Processor 5 Image Processor
- 5-Axis In-Body Image Stabilization
- 6.2K at 30 fps, 4K at 60 fps
- 19 Film Simulation Modes
- XC 15-45mm f/3.5-5.6 OIS PZ Lens



PRODUCT SPECIFICATIONS:

Imaging

Lens Mount	FUJIFILM X
Sensor Resolution	Effective: 26.1 Megapixel
Image Sensor	23.5 x 15.6 mm (APS-C) CMOS
Image Stabilization	Sensor-Shift, 5-Axis
Built-In ND Filter	None
Capture Type	Stills & Video
Exposure Control	

Shutter Type	Electronic Shutter, Mechanical Focal Plane Shutter
Shutter Speed	Mechanical Shutter 1/4000 to 900 Seconds in Manual Mode 1/4000 to 900 Seconds in Shutter Priority Mode 1/4000 to 30 Seconds in Program Mode 1/4000 to 30 Seconds in Aperture Priority Mode 0 to 60 Minutes in Bulb Mode
	Electronic Shutter 1/32000 to 900 Seconds in Manual Mode 1/32000 to 900 Seconds in Shutter Priority Mode 1/32000 to 30 Seconds in Program Mode 1/32000 to 30 Seconds in Aperture Priority Mode Fixed 1 Second in Bulb Mode
Bulb/Time Mode	None
ISO Sensitivity	Photo 160 to 12,800 in Manual, Auto Mode (Extended: 80 to 51,200)
	Video 125 to 12,800 in Manual, Auto Mode (Extended: 25,600)
Metering Method	Average, Center-Weighted Average, Multi, Spot, TTL 256-Zones
Exposure Modes	Aperture Priority, Manual, Program, Shutter Priority
Exposure Compensation	-5 to +5 EV (1/3 EV Steps)

White Balance	2500 to 10,000K Presets: Auto, Color Temperature, Custom, Fine, Fluorescent (Cool White), Fluorescent (Daylight), Fluorescent (Warm White), Incandescent, Shade, Underwater
	Electronic Shutter Up to 20 fps at 26.1 MP for up to 296 Frames (JPEG) / 28 Frames (Raw)
Continuous Shooting	Electronic Shutter Up to 10 fps at 26.1 MP for up to 341 Frames (JPEG) / 32 Frames (Raw)
	Electronic Shutter Up to 8 fps at 26.1 MP for up to 35 Frames (Raw)
Interval Shooting	Electronic Shutter Up to 30 fps at 20.9 MP for up to 407 Frames (JPEG) / 28 Frames (Raw)
	Electronic Shutter Up to 20 fps at 20.9 MP for Unlimited Frames (JPEG) / 30 Frames (Raw)
Interval Recording	Electronic Shutter Up to 10 fps at 20.9 MP for Unlimited Frames (JPEG) / 40 Frames (Raw)
	Mechanical Shutter Up to 8 fps at 26.1 MP for Unlimited Frames (JPEG) / 35 Frames (Raw)
Self-Timer	2/3/5/10-Second Delay
Still Image Capture	

Image Sizes	3:2
	6240 x 4160
	4416 x 2944
	3120 x 2080
	16:9
	6240 x 3512
	4416 x 2488
	3120 x 1760
	1:1
	4160 x 4160
2944 x 2944	
2080 x 2080	
Aspect Ratio	1:1, 3:2, 16:9
Image File Format	HEIF, JPEG, Raw, TIFF
Bit Depth	16-Bit

Internal Recording Modes	H.264 ALL-Intra/H.264 Long GOP/H.265/H.265 Long GOP/MOV/MP4/MPEG-4 AVC 4:2:2/4:2:0 8/10-Bit 6240 x 4160 at 23.98/24.00/25/29.97 fps (50 to 360 Mb/s) DCI 4K (4096 x 2160) at 23.98/24.00/25/29.97/50/59.94 fps (50 to 360 Mb/s) 2648 x 1630 at 23.98/24.00/25/29.97/50/59.94/100/120/200/240 fps (50 to 360 Mb/s) 1920 x 1080 at 23.98/24.00/25/29.97/50/59.94/100/120/200/240 fps (360 Mb/s)
	Raw/ProResRAW 12-Bit via HDMI 6240 x 4160 up to 29.97 fps
External Recording Modes	
Fast-/Slow-Motion Support	Yes
Recording Limit	None
IP Streaming	Yes
Built-in Microphone Type	Stereo
Audio Recording	MOV: 2-Channel 24-Bit 48kHz LPCM Audio MP4: AAC Audio

Media/Memory Card Slot	Single Slot SD/SDHC/SDXC (UHS-II 3 TB Maximum)
Video I/O	1x Micro-HDMI Output
Audio I/O	1x 1/8" / 3.5 mm TRS Stereo Microphone Input 1x 1/8" / 3.5 mm TRS Stereo Headphone Output
Other I/O	1x USB-C Control/Monitor/Inter
Wireless	2.4 GHz Wi-Fi (602 Hz/High), Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac) Yes: Android & iOS App Name: FUJIFILM XZ1
Mobile App Compatible	Free: FUJIFILM XZ1 app Functionality: Access, Stored Files, Adjust Settings, Firmware Update, Remote Control, View Live Feed *As of May 2023. Check with manufacturer for the most up-to-date compatibility.
Global Positioning (GPS, GLONASS, etc.)	None
Monitor	

Size	3"
Resolution	3 x 2 (1,840,000 Dot)
Display Type	Free-Angle Tilting Touchscreen LCD
Viewfinder	
Type	Built-In Electronic (OLED)
Size	0.39"
Resolution	2,360,000 Dot
Eye Point	17.5 mm
Coverage	100%
Magnification	Approx. 0.62x
Diopter Adjustment	-4 to +2
Focus	
Focus Type	Auto and Manual Focus
Focus Mode	Continuous-Servo AF, Manual Focus, Single-Servo AF
Autofocus Points	Contrast Detection, Phase Detection: 117
Flash	
Built-in Flash/Light	Yes, Flash Only
Guide Number	16.4' / 5 m at ISO 100
Maximum Sync Speed	1/180 Second
External Flash Connection	Hot Shoe, Proprietary
Environmental	
Operating Temperature	32 to 104°F / 0 to 40°C
Operating Humidity	10 to 80% (Non-Condensing)
General	
Battery Type	1 x NP-W235 Rechargeable Lithium-Ion
Tripod Mounting Thread	None
Dimensions (W x H x D)	5 x 3.4 x 2.6" / 127.7 x 85.1 x 65.4 mm
Weight	1.1 lb / 491 g (With Battery, Recording Media) 0.9 lb / 410 g (Body Only)
Packaging Info	
Package Weight	2.455 lb
Box Dimensions (LxWxH)	8.6 x 7.6 x 5.3"

FUJIFILM XF 18-55mm F/2.8-4 R LM OIS Lens Specs

Focal Length	18 to 55mm (35mm Equivalent: 27 to 84mm)
Maximum Aperture	f/2.8 to 4
Minimum Aperture	f/22
Lens Mount	FUJIFILM X
Lens Format Coverage	APS-C
Angle of View	79.1° to 28.4°
Minimum Focus Distance	11.81" / 30 cm
Maximum Magnification	0.15x
Optical Design	14 Elements in 10 Groups
Diaphragm Blades	7, Rounded
Focus Type	Autofocus
Image Stabilization	Yes
Filter Size	58 mm (Front)
Dimensions (ø x L)	2.56 x 2.77" / 65 x 70.4 mm
Length at Maximum Extension	3.85" / 97.8 mm
Weight	10.93 oz / 310 g
Packaging Info	
Package Weight	1.45 lb
Box Dimensions (LxWxH)	6.78 x 5.5 x 5.25"