



Republic of the Philippines
SOUTHERN LUZON STATE UNIVERSITY
Lucban, Quezon

REQUEST FOR QUOTATION

MULTI-POSITION HOT PLATE STIRRER (CAS)

Purchase Request No. 2024-02-0682
Approved Budget for the Contract: ₱200,000.00

The Southern Luzon State University through the Bids and Awards Committee invites interested firms/supplier to submit quotation for the procurement of **Multi-Position Hot Plate Stirrer (CAS)** to apply the sum of **Two Hundred Thousand Pesos Only (₱ 200,000.00)** inclusive of VAT, being the **Approved Budget for the Contract (ABC)**, details as follows:

Qty.	Unit	ITEM/S DESCRIPTION
4	unit	Multi-Position Hot Plate Stirrer
		*see attached document for specifications

1. The quotation must be submitted (can also be send thru email at the contact details listed below) or to the Office of the Procurement Office/Bids and Awards Committee, Southern Luzon State University, 2nd Flr. Hermano Puli Building, and shall be received by the Committee.

E-mail : slsuprocedurement2021@gmail.com

2. The SLSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/ informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. Southern Luzon State University SLSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.


MARIDEL C. ZABELLA
Head, Procurement Office
Southern Luzon State University
Lucban, Quezon
Tel. No.: (042)540-6519



Southern Luzon State University
College of Arts and Sciences
Laboratory

PURCHASE REQUEST

PHOTO REFERENCE



GENERAL FEATURES

Construction material: Epoxy painted metal structure

Heating plate: preferably carbon (if not, aluminium alloy) coated with a special protection

Heating plate diameter: 15mm

Stirring positions: 4 to 6

Power: 2550W

Weight: 8.3 Kg (18.2 lb)

Dimensions (WxHxD): 715x115x246 mm
(28.1x4.5x9.7 in)

Electric: 230 V / 50-60 Hz

PERFORMANCE

Electronic speed control: up to 1500 rpm for each stirring position

Temperature regulation: from room temp. to 370 °C for each stirring position

Stirring volume (H₂O): up to 2 liters per position

Stirring system: high-power driving magnet type "PCM" operated by a mono-phase motor for continuous operation

Counter-reaction: constant speed

Plate: Multi Round

Controls: Analog

ADDITIONAL

With magnetic stirrers included in the box