



Republic of the Philippines
SOUTHERN LUZON STATE UNIVERSITY
Lucban, Quezon

REQUEST FOR QUOTATION

SOUND SYSTEM FOR CTE AUDIO VISUAL ROOM (CTE)

Purchase Request No. 2024-02-0690

Approved Budget for the Contract: ₱490,256.00


The Southern Luzon State University through the Bids and Awards Committee invites interested firms/supplier to submit quotation for the procurement of **Sound System for CTE Audio Visual Room (CTE)** to apply the sum of **Four Hundred Ninety Thousand and Two Hundred Fifty Six Pesos Only (₱ 490,256.00) inclusive of VAT**, being the **Approved Budget for the Contract (ABC)**, details as follows:

Qty.	Unit	ITEM/S DESCRIPTION
5	pcs	Wireless Microphone
1	pcs	Snake Cable
1	pcs	Mixer
2	pcs	Speaker Stand
2	unit	Active Speaker
1	pcs	Flat Cord (1 roll)
10	pcs	Female Plug
10	pcs	Male Plug
10	pcs	Outlet with Grounded 3 Gang, Surface Type
2	unit	Uninterrupted Power Supply 3000 VA
2	unit	AVR 5000 Watts
4	unit	Portable Speaker
1	pcs	Camcorder
1	pcs	CamCorder / Video Microphone
1	pcs	Dual Channel Wireless Microphone System
1	pcs	Camcorder Tripod Heavy Duty
5	pcs	HDMI (10 Meter)
6	pcs	HDMI (5 Meter)
2	pcs	Heavy Duty Extension
6	pcs	Extension Wire (5 meter)

1. The quotation must be submitted (can also be send thru email at the contact details listed below) or to the Office of the Procurement Office/Bids and Awards Committee, Southern Luzon State University, 2nd Flr. Hermano Puli Building, and shall be received by the Committee.

E-mail : slsuprocedure2021@gmail.com

2. The SLSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/ informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. Southern Luzon State University SLSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.



MARIDEL C. ZABELLA
Head, Procurement Office
Southern Luzon State University
Lucban, Quezon
Tel. No.: (042)540-6519



**Republic of the Philippines
SOUTHERN LUZON STATE UNIVERSITY
Lucban, Quezon**

REQUEST FOR QUOTATION

Office/End-User: CTE	Date:
COMPANY NAME:	PR No.: 2024-02-0690
ADDRESS :	
TEL. NO./FAX NO. :	TIN No.:

Please quote your lowest price on the item(s) listed below, subject to the Terms & Conditions stated below and submit your quotation duly signed by your representative not later than _____ of _____ in the return envelope attached herewith to the Procurement office.

- TERMS and CONDITIONS**
1. All entries must be typewritten or legibility written.
 2. Delivery period within _____ upon conforme of the approved Purchase Order (P.O).
Administrative penalties to Sec. 69 of the Revised IRR-RA 1984 shall be imposed for non-delivery without valid reason.
 3. Warranty shall be for a minimum of three (3) months for Supplies & Materials; (1) one year for Equipment from date of acceptance by the end-user.
 4. Price validity shall be for a period of sixty (60) calendar days.
 5. Suppliers required to submit updated documents yearly such as G-EPSS Registration, Certificate of Tax, Mayor's Permit, DTI, Bank Name/Account and Branch for evaluation of the Procurement Office upon submission of the quotation.
 6. Bidders shall submit complete specifications showing products certification, if applicable.
 7. Please indicate the brand for each items being offered.
 8. The Approved budget ceiling for this procurement is PHP 490,256.00.

MARIDEL C. ZABELLA
Head, Procurement Office

Item #	Qty.	Unit	ITEM/S DESCRIPTION	Unit Price	Total Cost
	5	pcs	Wireless Microphone		
	1	pcs	Snake Cable		
	1	pcs	Mixer		
	2	pcs	Speaker Stand		
	2	unit	Active Speaker		
	1	pcs	Flat Cord (1 roll)		
	10	pcs	Female Plug		
	10	pcs	Male Plug		
	10	pcs	Outlet with Grounded 3 Gang, Surface Type		
	2	unit	Uninterrupted Power Supply 3000 VA		
	2	unit	AVR 5000 Watts		
	4	unit	Portable Speaker		
	1	pcs	Camcorder		
	1	pcs	CamCorder / Video Microphone		
	1	pcs	Dual Channel Wireless Microphone System		
	1	pcs	Camcorder Tripod Heavy Duty		
	5	pcs	HDMI (10 Meter)		
	6	pcs	HDMI (5 Meter)		
	2	pcs	Heavy Duty Extension		
	6	pcs	Extension Wire (5 meter)		

Source of Fund:	Warranty:
Delivery Period:	Price Validity:

After having carefully need & accepted your General Conditions, We quote you on the item(s) at prices note above. If the space of provided on the Delivery Period, Warranty & Price Validity are left blank, it means that I concur w/ the Terms & Conditions specified by SLSU Procurement Office.

Printed Name/Signature/Date



Southern Luzon State University
Lucban, Quezon


15000 php

ITEM	Specification	PRICE	QTY	AMOUNT
CAMCORDER	<ul style="list-style-type: none"> • Three 1/2" Exmor R CMOS Sensors • 4K 60p Recording • Integrated 17x Optical Zoom Lens • Electronic Variable ND Filter • Supports XAVC Intra/Long, MPEG HD, DVCAM • Supports S-Log 3 • Supports HLG for an HDR Workflow • Simultaneous 4K/HD Recording • 12G-SDI Output Supports 4K 60p • Built-In 2.4/5 GHz Wi-Fi 	387,542 php	1	387,542 php 157,757
CAMCORDER/Video Microphone	<ul style="list-style-type: none"> • High-quality directional on-camera microphone • Supercardioid polar pattern • Two-stage gain control, high-pass filter (80Hz) • Integrated Rycote Lyre shock mounting • Sensitivity scopes 38.0dB re 1 Volt/Pascal (12.60mV @ 94 dB SPL) +/- 2 dB @ 1kHz • Frequency Range scopes +0Hz - 20kHz 	4500 php	1	4500 php

<p>Dual Channel Wireless Microphone System</p> <p>RODE GO WIRELESS MIC</p>	<ul style="list-style-type: none"> • sources simultaneously • Series IV 2.4GHz digital transmission, 128-bit encryption – crystal-clear audio at up to 200m (line of sight), optimised for extremely stable operation in dense RF environments • 3.5mm TRS analog output, USB-C and iOS digital output – universal compatibility with cameras, mobile devices and computers • On-board recording – over 40 hours of internal memory • Option to record each channel separately or combine them for ultimate flexibility in post-production • Safety channel, flexible gain control (three-stage pad, expandable to 10-stage) • In-built rechargeable lithium-ion battery – up to 7 hours battery life 	<p>15 000 php</p>	<p>1</p>	<p>15000 php</p>
--	--	-------------------	----------	------------------

Camcorder Tripod Heavy Duty	<ul style="list-style-type: none"> • High-strength aluminum alloy double-row tube and 60mm bowl base provide better stability. The mid-level spreaders keep the legs from collapsing on uneven ground and add stability with adjustable rubber mats. • The head can rotate 360° horizontally. The built-in damping and dynamic balancing system make fluid head operated smooth, can tilt +90°/-75° vertically and the max load is 13.2 lbs. 	3000 php	1	3000php
-----------------------------	--	----------	---	---------

Pictures of Items



Heavy Duty Tripod



Camcorder




Video Microphone



Wireless Microphone

Pictures of Items



Heavy Duty Tripod



Camcorder



Video Microphone



Wireless Microphone

Portable Speaker (P 15,000.00)

- 450Watts
- 15" x 2 pcs. Woofer
- Plastic Cabinet
- AC220V or DC12V (With built-in Rechargeable Batteries)
- With 2 Wireless Microphone
- With 2 Mic Input (1 XLR, 1 PL55)
- With FM Radio, Bluetooth, Guitar Input (Shared with Mic 2 input), USB & SD Port
- With 5 Band Equalizer and LCD Display
- With Aux / Line In and Line Out
- With Remote Control, Handle and Wheels
- One piece per order

450Watts 15" x 2 pcs. Woofer Plastic Cabinet
AC220V or DC12V (With built-in
Rechargeable Batteries) With 2 Wireless
Microphone With 2 Mic Input (1 XLR, 1 PL55)
With FM Radio, Bluetooth, Guitar Input
(Shared with Mic 2 input), USB & SD Port
With 5 Band Equalizer and LCD Display With
Aux / Line In and Line Out With Remote
Control, Handle and Wheels One piece per
order

PICTURES



Wireless Microphone

Dynamic



Mixer



1 Roll Microphone Cable



1 Roll Instrument Cable



Male and Female XLR plug



Speaker Stand



Active Speaker



Flat Cord #18



Male Plug Outlet

Extension Universal Outlet with Ground 3 Gang, Surface Type Outlet with Ground 3 Gang Universal



Outlet with Ground



Uninterruptible Power Supply 3,000 VA



AVR 5000 Watts

ITEM	SPECIFICATION
Wireless Microphone	Clear sound quality and rock-solid, dependable performance / Automatic frequency scanning finds an open channel at the touch of a button / All 10 user-switchable channels are compatible, for easy use with multiple systems / 9 hours average battery life, 2 x AA alkaline / True Diversity operation selects the better signal from the two receiver sections, reducing dropout
1 Roll Microphone Cable	Oxygen-free copper (OFC) Conductors for Enhanced signal clarity / Hi-density OFC Braided Shield for superior EMI and RFI Rejection
Male XLR	3-Pin XLR Male
Female XLR	adapt a balanced phone plug to an XLR input / Connector(s): 1/4 in TRS to XLR3M / 1/4" to male xlr
Mixer	10-Channel Mixing Console / Max. 4 Mic / 10 Line Inputs (4 mono + 3 stereo) / 1 Stereo Bus / 1 AUX (incl. FX) / "D-PRE" mic preamps with an inverted Darlington circuit / 1-Knob compressors / High-grade effects: SPX with 24 programs / 24-bit / 192kHz 2in / 2out USB Audio functions / Works with the iPad (2 or later) through the Apple iPad Camera Connection Kit / Lightning to USB Camera Adapter / Includes Cubase AI DAW software download version / Cubasis LE for iPad available at App Store / PAD switch on mono inputs / +48V phantom power / XLR balanced outputs / Metal chassis / Dimensions(W×H×D): 244 mm x 71 mm x 294 mm (9.6"x 2.8"x 11.6") / Net Weight: 2.1 kg (4.63 lbs.)
Speaker Stand	Aluminium tubing for strength and lightness / Super durable and holds up to 45kg (100lbs) / Height: 128-205cm (50.4-80.7") / Weight: 2.3kg (5.1lbs) / Base diameter:132cm (51.97") / Load capacity: 45kg (100lbs) / Accepts flanges: 35, 38mm (1 3/8, 1 1/2") / Folded size: 113x15cm (44.5x5.9") / Two stands and a carrying bag / Specifically designed for touring musicians, backline and rental companies / Patent pending Smart Adaptor quickly converts between 35mm and 38mm speaker poles.

	One-piece design has no loose parts / Aluminum tubing for strength and lightness / Super durable and holds up to 45kg (100lbs)
Active Speakers	2000 W peak (1300 LF + 700 HF) 1000 W continuous RMS (650 LF + 350 HF) 8-inch (203 mm) LF driver, 2.5-inch (65 mm) high-temperature voice coil HF Driver: 1.4-inch (35 mm) neodymium magnet HF driver with precision waveguide High quality, lightweight, cabinet design for easy transport, set up and installation Pole-mountable, wedge monitor, bracket installation or flown application with integral M6 suspension points Integrated 2-channel mixer with dual XLR 1/4-inch combo mic/line inputs, independent level controls, XLR Link output, Contour EQ switch and Ground-Lift switch Custom-engineered high-efficiency class D amplifiers with passive cooling design – no fan means the speaker runs cleaner, quieter and has greater long-term reliability
1 Roll Flat Cord	Flat Cord
Male Plug	Plug
Outlet w/ Ground 3 Gang, Surface Type Outlet w/ Ground 3 Gang w/ Ground	Ground 3 Gang, Surface Type Outlet w/ Ground 3 Gang w/ Ground
Uninterruptible Power Supply 3,000 VA	3,000 VA
AVR 5000 Watts	5,000 watts