

Republic of the Philippines SOUTHERN LUZON STATE UNIVERSITY Lucban, Quezon

REQUEST FOR QUOTATION

COMPUTER ACCESSORIES (CATANAUAN)

Purchase Request No. 2024-08-1646
Approved Budget for the Contract: 2-312,800.00

The Southern Luzon State University through the Bids and Awards Committee invites interested firms/supplier to submit quotation for the procurement of Computer Accessories (Catanauan) to apply the sum of Material States inclusive of VAT, being the Approved Budget for the Contract (ABC), details as follows:

Qty.	Unit	ITEM/S DESCRIPTION	
2	pcs	SMART-UPS SRT 1500VA 230V - Output power: 1500W Input operation voltage (min): 100V Input operation voltage (max): 275V Output operation voltage (min): 220V Output operation voltage (max): 240V Surge energy rating: 432 J Emergency Power Off (EPO): Yes Crest factor: 3:01 Output power capacity: 1500VA Cable length: 1.83m UBS port: Yes Serial interface type: RJ-45 Noise level: 50dB Output frequency: 50/60 Hz Input frequency: 40/70 Hz Battery life (max): 5 years Battery technology: Sealed Lead Acid (VRLA) Battery recharge time: 3h	
1	pcs	CR-M4 3D PRINTER - Printing technology: FDM Build Volume: 450*450*470mm Product dimensions: 655*700*865mm Package dimensions: 790*760*300mm Net Weight: 22.48kg Gross Weight: 28.3kg Printing speed: ≤120mm/s Printing Accuracy: ±0.1mm Layer Height: 0.05-0.35mm Extruder Type: "Sprite" dual-gear direct drive extruder Filament Diameter: 1.75mm Z-axis count: 2 Nozzle type: Brass nozzle Nozzle Diameter: Standard 0.4mm (compatible with 0.6/0.8mm) Nozzle temperature: ≤300°C Heatbed Temperature: ≤100°C Build Surface: PC spring steel sheet Display Screen: 4.3-inch color touch screen Mainboard: Integrated 32-bit silent mainboard Rated Voltage: 100-240V~. 5-/60Hz Rated Power: 800W Slicing Software: Creality Print, Creality Slicer, Cura File Formats: STL, OBJ, AMF Supported Filaments: PLA, PETG, TPU, ABS, PLA-Wood, PA, PLA-CF	
1	pcs	K1 MAX 3D PRINTER - Printing Technology: FDM Build Volume: 300*300*300mm Product dimensions: 435*462*526mm Package dimensions: 508*508*608mm New Weight: 18kg Gross Weight: 23kg Printing speed: ≤600mm/s Acceleration: ≤20000mm/s² Printing Accuracy: 100±0.1mm Layer height: 0.1-0.35mm Extrude Dual-gear direct drive extruder Filament Diameter: 1.75mm Nozzle diameter: 0.44 (compatible with 0.6/0.8mm) Nozzle Tamp: ≤300°C Heathed Tamp: ≤400°C Pacilical Policy Pacilical Policy	

*see attached picture for reference	
*deliver to SLSU Catanauan Campus	

1. The quotation must be submitted (can also be send thru email at the contact details listed below) or to the Office of the Procurement Office/Bids and Awards Committee, Southern Luzon State University, 2nd Flr. Hermano Puli Building, and shall be received by the Committee.

E-mail: slsuprocurement@slsu.edu.ph

2. The SLSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/ informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. Southern Luzon State University SLSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.

MARIDEL C. ZABELLA Head, Procurement Office Southern Luzon State University Lucban, Quezon Tel. No.: (042)540-6519



Republic of the Philippines SOUTHERN LUZON STATE UNIVERSITY Lucban, Quezon

REQUEST FOR QUOTATION

	nd-User:		SLSU Catanauan	Date:		
ADDRE	ANY NAN			PR No.:	2024-08-1646	
	O./FAX N			TIN No.:	material de la companya del companya de la companya del companya de la companya d	
			The second secon	TIN NO		
n			lowest price on the item(s) listed below, subject to the Terms & Conditions strain in the return envelope attached herewith to the Proceedings of the Procedings of the Proceedings of the Procedings of the Procedings of the Proceedings of the Procedings of	tated below and submit your quotation duly signer ocurement office.	d by your representative not la	
5. Suppliers required to submit updated documents yearly such as G-EPS Resgistration, Head, F					DEL C. ZABELLA Procurement Office	
Procurer 6. Bidde 7. Pleas	ement Office ers shall sub se indicate ti	e upon subn bmit comple the brand fo	rmit, DTI, Bank Name/Account and Branch for evaluation of the mission of the quotation. Ilete specifications showing products certification, if applicable. If for each items being offered. Ing for this procurement is			
em#	Qty.	Unit	ITEM/S DESCRIPTION	Unit Pr	rice Total Cost	
	2	pcs	SMART-UPS SRT 1500VA 230V - Output power: 1500W Input of Input operation voltage (max): 275V Output operation voltage operation voltage (max): 240V Surge energy rating: 432 J Eme Crest factor: 3:01 Output power capacity: 1500VA Cable leng Serial interface type: RJ-45 Noise level: 50dB Output frequency frequency: 40/70 Hz Battery life (max): 5 years Battery techno (VRLA) Battery recharge time: 3h	operation voltage (min): 100V e (min): 220V Output ergency Power Off (EPO): Yes igth: 1.83m UBS port: Yes cy: 50/60 Hz Input		
	1	pcs	CR-M4 3D PRINTER - Printing technology: FDM Build Volume: 4th dimensions: 655*700*865mm Package dimensions: 790*760*3 22.48kg Gross Weight: 28.3kg Printing speed: ≤120mm/s Pri Layer Height: 0.05-0.35mm Extruder Type: "Sprite" dual-gear dimensional dimenter: 1.75mm Z-axis count: 2 Nozzle type: Brass Standard 0.4mm (compatible with 0.6/0.8mm) Nozzle temperat Temperature: ≤100°C Build Surface: PC spring steel sheet Disp touch screen Mainboard: Integrated 32-bit silent mainboard R /60Hz Rated Power: 800W Slicing Software: Creality Print, Creaformats: STL, OBJ, AMF Supported Filaments: PLA, PETG, TPU, A	300mm Net Weight: inting Accuracy: ±0.1mm irect drive extruder s nozzle Nozzle Diameter: iture: ≤300°C Heatbed play Screen: 4.3-inch color Rated Voltage: 100-240V∼. 5- eality Slicer, Cura File		
	1	pcs	K1 MAX 3D PRINTER - Printing Technology: FDM Build Volume: 3 dimensions: 435*462*526mm Package dimensions: 508*508*6 Gross Weight: 23kg Printing speed: ≤600mm/s Acceleration: ≤ Accuracy: 100±0.1mm Layer height: 0.1-0.35mm Extruder: Dui Filament Diameter: 1.75mm Nozzle diameter: 0.4mm (compat Nozzle Temp: ≤300°C Heatbed Temp: ≤100°C Build Surface: Fle Mode: Hands-free auto leveling File Transfer: USB drive, Etherne 4.3" color touch screen Al Camera: Yes Filament Runout Senso 240√, 50/60Hz Rated power: 1000W Supported Filaments: Pl ASA, PC, PLA-CF, PA-CF, PET-CF Printable File Format: G-Code SPrint; compatible with Cura, Simplify3D, PrusaSlicer File Formats	508mm Net Weight: 18kg 52000mm/s² Printing ual-gear direct drive extruder tible with 0.6/0.8mm) lexible build plate Leveling net, WiFi Display Screen: or: Yes Rated Voltage: 100- PLA,PETG, PET, TPU, PA, ABS, Slicing Software: Creality		
			*see attached picture for reference			
			*deliver to SLSU Catanauan Campus			
ource c	of Fund: Period:		PRE CATANAUAN	Warranty: Price Validity		

AFA-PRC-1.02 F2, REV. 4

Printed Name/Signature/Date

SMART-UPS SRT 1500VA 230V





CR-M4 3D Printer



K1 Max AI Fast 3D Printer

