



Republic of the Philippines
SOUTHERN LUZON STATE UNIVERSITY
Lucban, Quezon

REQUEST FOR QUOTATION

RADIATION METER (CEN)

Purchase Request No. 2025-01-0097

Approved Budget for the Contract: ₱ 55,000.00


The Southern Luzon State University through the Bids and Awards Committee invites interested firms/supplier to submit quotation for the procurement of **Radiation Meter (CEN)** to apply the sum of **Fifty-Five Thousand Pesos Only (₱ 55,000.00)** inclusive of VAT, being the **Approved Budget for the Contract (ABC)**, details as follows:

Qty.	Unit	ITEM/S DESCRIPTION
1	pc	Radiation Meter
		*see attached document for specifications

1. The quotation must be submitted (can also be send thru email at the contact details listed below) or to the Office of the Procurement Office/Bids and Awards Committee, Southern Luzon State University, 2nd Flr. Hermano Puli Building, and shall be received by the Committee.

E-mail : slsuprourement@slsu.edu.ph

2. The SLSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/ informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. Southern Luzon State University SLSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.


MARIDEL C. ZABELLA
Director, Procurement Office
Southern Luzon State University
Lucban, Quezon
Tel. No.: (042)540-6519



Units	CPS, CPM, uSv/hr with autorange
Display	Clear backlit LCD display
Controls	Power, up, down, OK (menu keys)
Environmental	Operating temperature -10°C to +50°C Storage temperature -25°C to +60°C
Power	Lithium Ion rechargeable, typically >12 hours continuous use. Charger supplied
Cleaning	Radhound is chemical resistant, and can be cleaned with Alcohol wipes
Range	Typically 0 - to 99999 counts per second (range and units are software selectable depending on probe)
Response Time	0.5 seconds
Functionality	Rate, histogram, timed count, count to time, time remaining to dose, alpha beta discrimination (depending on probe)
High Voltage	350 - 1200v selectable in menu (can be locked)
Averaging	'Smart Averaging' provides fluid number change, whilst retaining a response time adjustable between slow, medium and fast
Mechanical	Dimensions 160 x 250 x 85 mm approx (with stand)