



Republic of the Philippines
SOUTHERN LUZON STATE UNIVERSITY
Lucban, Quezon



REQUEST FOR QUOTATION

SPEAKERS AND MICROPHONE (GS)

Purchase Request No. 2025-01-0093
Approved Budget for the Contract: ₱ 290,000.00

The Southern Luzon State University through the Bids and Awards Committee invites interested firms/supplier to submit quotation for the procurement of Speakers and Microphone (GS) to apply the sum of Two Hundred Ninety Thousand Pesos Only (₱ 290,000.00) inclusive of VAT, being the **Approved Budget for the Contract (ABC)**, details as follows:

Qty.	Unit	ITEM/S DESCRIPTION
5	pcs	Speakers (Wall Mount)
20	pcs	Gooseneck Cardioid Microphone
		note: w/ product quality certification, pref. branded item, w/ warranty & w/ installation
		*see attached document for specifications

1. The quotation must be submitted (can also be send thru email at the contact details listed below) or to the Office of the Procurement Office/Bids and Awards Committee, Southern Luzon State University, 2nd Flr. Hermano Puli Building, and shall be received by the Committee.

E-mail : slsuprourement@slsu.edu.ph

2. The SLSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/ informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. Southern Luzon State University SLSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.


MARIDEL C. ZABELLA
Director, Procurement Office
Southern Luzon State University
Lucban, Quezon
Tel. No.: (042)540-6519



Wall mount speaker

13.5" H x 5.75" W x 8" D

Sound Options: Stereo

Entire Product System: 17.031 lb

Product Material: Metal, Plastic

Impressive sound for extreme weather

Lifelike sound even outdoors

© 2011 JBL Corporation. Model A-01
JBL is a registered trademark of JBL Corporation.



- Operating voltage: 100-240 VAC, 50/60 Hz (auto-switching)
- Current consumption: MAX 0.9A (100VAC) 0.3A (240VAC)
- DC supply to contribution units: $\pm 15\text{V}$ Line, Telephone Coupler and Insertion
- In/Outputs (Unbalanced)
 - Input sensitivity: $-14\text{dBV}/+11\text{dBV}$ (nominal/maximum)
 - Input impedance: 33Kohm
 - Output level: $-14\text{dBV}/+11\text{dBV}$ (nominal/maximum)
 - Output impedance: 500ohm
- Recorder In/Out (Unbalanced)
 - Input sensitivity: $-20\text{dBV}/+5\text{dBV}$ (nominal/maximum)
 - Input impedance: 47Kohm (for L & R channel)
 - Adjustment: $-20\text{dBV}/+5\text{dBV}$
 - Output level: $+0/-30\text{dB}$
 - Output impedance: 500ohm
- External Microphone Input (Balanced)
 - Input sensitivity: -56dBV
 - Adjustment: $+6\text{dB}/-6\text{dB}$
 - Phantom Power: $12\text{V}/-1\text{V}$, $2 \times 680\text{ohm}$ ($\pm 2\%$)
 - Output connection: 3.5mm stereo jack
- Headphone Output
 - Output level: $-8\text{dBV}/+2\text{dBV}$
 - Output Impedance: 22ohm
- Temperature range

Storage and transport: -4 to 131°F / -20 to 55°C

Operating temperature: 41 to 113°F / 5 to 45°C

- Ambient humidity

Storage and transport: 0% – 99% RH

Operational: 20% -95% RH

- Dimensions (HxWxD): 360 X 150 X 90 mm

- Weight: 2 lbs 11 oz / 1215 g