



Republic of the Philippines  
**SOUTHERN LUZON STATE UNIVERSITY**  
Lucban, Quezon

**REQUEST FOR QUOTATION**

**CCTV CAMERA (CSSU)**

**Purchase Request No. 2025-01-0120**  
**Approved Budget for the Contract: ₱ 64,000.00**

The Southern Luzon State University through the Bids and Awards Committee invites interested firms/supplier to submit quotation for the procurement of **CCTV Camera (CSSU)** to apply the sum of **Sixty-Four Thousand Pesos Only (₱ 64,000.00)** inclusive of VAT, being the **Approved Budget for the Contract (ABC)**, details as follows:

Qty.	Unit	ITEM/S DESCRIPTION
20	pcs	CCTV Camera
		*see attached document for specifications

1. The quotation must be submitted (can also be send thru email at the contact details listed below) or to the Office of the Procurement Office/Bids and Awards Committee, Southern Luzon State University, 2<sup>nd</sup> Flr. Hermano Puli Building, and shall be received by the Committee.

E-mail : [slsuprocurement@slsu.edu.ph](mailto:slsuprocurement@slsu.edu.ph)

2. The SLSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/ informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. Southern Luzon State University SLSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.

  
**MARIDEL C. ZABELLA**  
Director, Procurement Office  
Southern Luzon State University  
Lucban, Quezon  
Tel. No.: (042)540-6519





## **CCTV Camera**

### **Specification:**

#### **Camera:**

Max. Resolution - 2560 × 1440, Min.  
Illumination Color - 0.01 Lux @(F2.0, AGC ON), B/W: 0 Lux with IR  
Shutter Time - 1/3 s to 1/100,000 s  
Day & Night - IR cut filter  
Angle Adjustment Pan - 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°

#### **Lens:**

Lens Type - Fixed focal lens, 2.8 and 4 mm optional  
Focal Length & FOV - 2.8 mm, horizontal FOV 99°, vertical FOV 55°, diagonal FOV 116° 4 mm,  
horizontal FOV 76°, vertical FOV 41°, diagonal FOV 90°  
Lens Mount - M12  
Iris Type - Fixed  
Aperture - F2.0

#### **Illuminator:**

Supplement Light Type - IR  
Supplement Light Range - Up to 30 m  
Smart Supplement Light - Yes  
IR Wavelength - 850 nm

#### **Interface:**

Ethernet Interface - 1 RJ45 10 M/100 M self-adaptive Ethernet port

#### **Video:**

Main Stream - 50 Hz: 20 fps (2560 × 1440); 25 fps (1920 × 1080, 1280 × 720)  
60 Hz: 20 fps (2560 × 1440); 24 fps (1920 × 1080, 1280 × 720)

Sub-Stream - 50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360)  
60 Hz: 24 fps (1280 × 720, 640 × 480, 640 × 360)

Video Compression - Main stream: H.265+/H.265/H.264+/H.264  
Sub-stream: H.265/H.264/MJPEG

Video Bit Rate - 32 Kbps to 8 Mbps

#### **Event:**

Basic Event - Motion detection (support alarm triggering by specified target types (human and vehicle)), video tampering alarm, exception  
Linkage - Upload to FTP, send email, notify surveillance center, trigger capture