



Republic of the Philippines  
**SOUTHERN LUZON STATE UNIVERSITY**  
Lucban, Quezon



**REQUEST FOR QUOTATION**

**COMPUTER LABORATORY SUPPLIES (CATANAUAN)**

**Purchase Request No. 2025-10-2504**  
**Approved Budget for the Contract: ₱ 95,000.00**


The Southern Luzon State University through the Bids and Awards Committee invites interested firms/supplier to submit quotation for the procurement of **Computer Laboratory Supplies (Catanauan)** to apply the sum of **Ninety-Five Thousand Pesos Only (₱ 95,000.00)** inclusive of VAT, being the **Approved Budget for the Contract (ABC)**, details as follows:

Qty.	Unit	ITEM/S DESCRIPTION
10	set	21.5" Computer LED Monitor
10	pcs	Analog Multi-Tester

1. The quotation-n must be submitted (can also be send thru email at the contact details listed below) or to the Office of the Procurement Office/Bids and Awards Committee, Southern Luzon State University, 2<sup>nd</sup> Flr. Hermano Puli Building, and shall be received by the Committee.

E-mail : [slsuprourement@slsu.edu.ph](mailto:slsuprourement@slsu.edu.ph)

2. The SLSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/ informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. Southern Luzon State University SLSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.

  
**MARIDEL C. ZABELLA**  
Director, Procurement Office  
Southern Luzon State University  
Lucban, Quezon  
Tel. No.: (042)540-6519b





Unit	Item Description	Quantity					
SETS	<table><tr><td>21.5 " Computer LED Monitor</td></tr><tr><td>Full HD (1920 x 1080) 75 Hz,</td></tr><tr><td>Inputs: HDMI, VGA,</td></tr><tr><td>Response Time: 1 ms VRB, Brightness: 250 Nit</td></tr><tr><td>with cables and other accessories</td></tr></table>	21.5 " Computer LED Monitor	Full HD (1920 x 1080) 75 Hz,	Inputs: HDMI, VGA,	Response Time: 1 ms VRB, Brightness: 250 Nit	with cables and other accessories	10
21.5 " Computer LED Monitor							
Full HD (1920 x 1080) 75 Hz,							
Inputs: HDMI, VGA,							
Response Time: 1 ms VRB, Brightness: 250 Nit							
with cables and other accessories							
pcs	<p><b>ANALOG MULTI-TESTER</b> Specs and Function Measuring range Tolerance Drop shock-proof meter Null(zero center) meter <math>\pm 5 / \pm 25</math> in DCV High resistance up to 200M<math>\Omega</math> with low voltage Protective body cover Capacitance, dB, Li measurement DCV 0.1 (20k<math>\Omega</math>/V) 0.25/2.5/10/50 (20k<math>\Omega</math>/V)/250/1000V (9k<math>\Omega</math>/V) <math>\pm 5\%</math> of full scale <math>\pm 3\%</math> of full scale DCV (NULL) <math>\pm 5/25V</math> (40k<math>\Omega</math>/V) <math>\pm 5\%</math> of full scale ACV 10/50/250/750 (9k<math>\Omega</math>/V) <math>\pm 4\%</math> of full scale DCA 50<math>\mu</math>/2.5m/25m/0.25A * 1 <math>\pm 3\%</math> of full scale Resistance 2k/20k/200k/2M<math>\Omega</math> (x1/x10/x100/x1k) 200M<math>\Omega</math> (x100k) <math>\pm 3\%</math> of arc <math>\pm 5\%</math> of arc</p> <p>Capacitance 10<math>\mu</math>F Approximate value dB -10dB <math>\sim</math> +22dB (for 10VAC) <math>\sim</math> +62dB Approximate value Load current (LI) 0-150m/15m/1.5m/150<math>\mu</math>/1.5<math>\mu</math>A Approximate value DC high voltage DC25kV (optional probe "HV-10T" is necessary) - hFE 1000 at x10 range (optional probe "HFE-6T" is necessary) - Battery R6 (IEC) or UM-3 (1.5V)x2 Fuse <math>\Phi 5.2 \times 20</math>mm (250V/0.5A)</p> <p style="text-align: right;">Size/Mass</p> <p>H159.5xW129xD41.5mm/Approx. 320g ※ The value in ( ) at DCV and ACV is input resistance</p> <p>*including the resistance of fuse and accessories.</p>	10					