



Republic of the Philippines
SOUTHERN LUZON STATE UNIVERSITY
Lucban, Quezon



REQUEST FOR QUOTATION

LIVELIHOOD EQUIPMENT FOR E-CEST PROJECT (VPREPDI-ECEST)

Purchase Request No. 2026-07-1813

Approved Budget for the Contract: ₱ 420,000.00

The Southern Luzon State University through the Bids and Awards Committee invites interested firms/supplier to submit quotation for the procurement of **Livelihood Equipment for E-CEST Project (VPREPDI-ECEST)** to apply the sum of **Four Hundred Twenty Thousand Pesos Only (₱ 420,000.00)** inclusive of VAT, being the **Approved Budget for the Contract (ABC)**, details as follows:

Qty.	Unit	ITEM/S DESCRIPTION
1	unit	Coconut Husk Decorticator
2	unit	Twining Machine

1. The quotation must be submitted (can also be sent thru email at the contact details listed below) or to the Office of the Procurement Office/Bids and Awards Committee, Southern Luzon State University, 2nd Flr. Hermano Puli Building, and shall be received by the Committee.

E-mail : slsuprourement@slsu.edu.ph

2. The SLSU reserves the right to reject any or all quotations and/or proposals and waive any formalities/ informalities therein and to accept such bids it may consider as most advantageous to the agency and to the government. Southern Luzon State University SLSU neither assumes any obligation for whatsoever losses that may be incurred in the preparation of bids, nor does it guarantee that an award will be made.

MARIDEL C. ZABELLA
Director, Procurement Office
Southern Luzon State University
Lucban, Quezon
Tel. No.: (042)540-6519

Coconut Husk Decorticator w Wood Chipper Trailer Type Specifications:

- Capacity: 500-800 kgperhour(Fresh Materials)
- Capacity : 200-500 kg per hour (Dry Materials)
- Input materials: 3 inches Wood Diameter, Coconut Husk (bunot/buko) , Leaves , Paper , Grass, Small Twigs & Other Farm Waste
- Dual Output Chute for Separating Fiber & Cocopeat
- Adjustable Prime Mover Frame for Easy Belt Adjustment Prime Mover: 12HP Yamma Air Cooled Diesel Engine

TWINE MAKING MACHINE Specification:

- Motor Type - Single-phase or three-phase squirrel cage induction motor;
- Power Rating - 1.5 HP (Horsepower);
- Voltage - 220V / 380V (depending on local supply); Speed - 1440 RPM ($\pm 5\%$);
- Cooling - Air cooled with fan cover;
- Mounting - Base-mounted with flange option;
- Protection - IP44 minimum, TEFC (Totally Enclosed Fan Cooled
- Pulley System - 6-pulley system (steel or cast iron) with standard taper lock bushings;
- V Belts - Industrial grade V-belts, size B or A as per load requirements;
- Pillow Block Bearings - 2-4 heavy-duty pillow block bearings (UC or UCP type)
- Main Frame - Galvanized Iron (GI) sheet metal (thickness: 2.0 mm min.);
- Structural Support - Angle bar (L-shape) 1.5" $\times$ 1.5" $\times$ 3mm;
- Base Frame - Welded angle bar framework with anti-vibration rubber feet;
- Spindle Material - Mild steel or aluminum alloy, balanced for high-speed rotation